# Desk/1600

Clever consumer-facing PINPad for a seamless self-checkout at counter







# The Desk/1600 handles all payment methods and allows for intuitive contactless interaction with your customer. The compact design allows use of limited space on your counter.

## Optimized checkout time

Payment validation is more efficient with the intuitive and easy to use Desk/1600. The clearly marked contactless zone allows for reduced transaction times.

### Designed for a limited space

The compact Desk/1600 fits easily on any counter, with options for either a mounted or unmounted terminal to suit the available desktop space.

# **Highest security**

The Desk/1600 is certified and fully compliant with the latest global and local PCI regulations to ensure long-term payment security compliance – protecting customers' data for years to come.



With plug-and-play installation and USB connection, the Desk/1600 connects to any Desk/series device, offering a speedy and unified solution.

### Compatible with Ingenico's suite of services

The Desk/1600 works in unison with Ingenico's supporting service platforms, meaning merchants will have access to business services such as back office reporting. Software updates and day-to-day support deliver a hassle-free experience.

15

The Desk/1600 is supported by our Cloud Services





	DESK/1600		
Processor	Application     & Crypto processor	• Cortex 32bit – 160 Mhz	⊘
Memory	• Internal	• 700 KB RAM, 2 MB Flash	<ul> <li></li> </ul>
os		• Telium TETRA	•
Card readers	<ul> <li>Magstripe</li> <li>Smart card</li> <li>Contactless</li> </ul>	ISO 1/2/3, 500K lifespan     EMV Level 1, 500K lifespan     EMV Level 1, v.3	<ul> <li></li> <li></li> <li></li> <li></li> </ul>
Display	Color	<ul> <li>2.8" display, QVGA (320×240 pixels) - Glass lens</li> </ul>	<
Keypad		<ul> <li>15 keys, raised marking, 4 function keys</li> </ul>	<ul> <li></li> </ul>
Audio	• Buzzer		<ul> <li></li> </ul>
Terminal connections	• USB	• 1 USB Host	×

			DESK/1600
Terminal size		• 7.08×3.26×1.69" (180.2×83.2×43 mm)	~
Weight		• 7.79oz (221 g)	<
Environment	Operating Temperature     Storage Temperature     Operating Humidity	<ul> <li>32°F to 104°F (0°C to +40°C)</li> <li>-4°F to 131°F (-20°C to +55°C)</li> <li>85% non-condensing at 104°F (+40°C)</li> </ul>	<ul><li></li><li></li><li></li></ul>
Accessory	Privacy shield	Factory mounted     Field upgradable	Optional Optional
Security		PCI PTS 6.x online     & offline certified	•



